




289.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel® Bay Trail Celeron® Processor J1900 2.0G Quad Core
- Integrated Intel® HD Graphics, VGA interface
- Max. Resolution 2560 x 1600/60Hz
- Support DDR3L 1333MHz Single Channel
- Onboard 4GB System Memory
- 4 * Intel i211AT PCIe GbE LAN
- 1 * Serial ATAll (3Gb/s)
- 1 * External COM (RS232), 1 * Internal COM (RS232)
- 1 * External USB3.0, 1 * USB1.1/2.0, 2 * Internal USB1.1/2.0
- 2 * Full size mPCIe, 1 * Full size mPCIe shared with mSATA
- 1 * SIM Card Holder
- Lockable DC-in PWR JACK
- 3.5" Form Factor (148mm x 102mm)

Product Specifications

Form Factor	
Dimensions	- 3.5" Form Factor (148 x 102mm)
Processor System	
CPU	- Intel® Bay Trail Celeron® Processor J1900, TDP : 10W
Core Number	- Quad Core
Speed	- Processor Base Frequency : 2.0GHz, Burst Frequency : 2.42GHz
L2 Cache	- 2MB
Chipset	- SoC
BIOS	- AMI 64Mb Flash ROM
Expansion Slot	
PCI	- 0
PCIe	- 0
Memory	
Technology	- Single Channel DDR3L 1333MHZ

Max.		- 4GB	
Socket		- 0 (Memory Onboard)	
Graphics			
Controller / VRAM		- Intel® HD Graphics / Shared system memory	
VGA		- Yes (Max. Resolution : 2560X1600@60Hz)	
DVI		- No	
HDMI		- No	
DisplayPort		- No	
eDP		- No	
LVDS		- No	
MultiDisplay		- No	
Ethernet			
Interface		- 10/100/1000 Mbps	
Controller		- PCIe GbE LAN: Intel i211AT	
Connector		- 4 * RJ 45	
Audio			
CODEC		- No	
Channel		- No	
SATA			
Max. Data Transfer Rate		- 1 * SATAII (3.0Gb/s)	
RAID Support		- No	
Rear I/O			
VGA	- 0	SPDIF Output	- 0
DVI	- 0	Serial	- 1 (RS232)
HDMI	- 0		
DisplayPort	- 0	Parallel	- 0
Ethernet	- 4	eSATA	- 0
USB	- 2 (1*USB3.0, 1*USB1.1/2.0)	PS2	- 0
Audio	- 0	DC-Input	- 1 (12V Lockable DC-In PWR Jack)
Internal Connector			
USB	- 2 (USB1.1/2.0)	SIM Card Holder	- 1
PS/2	- 1	CFast Card Socket	- 0
LVDS /	- 0	CF Card Socket	- 0
Inverter		CIR	- 0
VGA	- 1	GPIO 8-bit	- 1 (4in/4out)
Serial	- 1	Chassis intrusion	- 1
	(RS232 with 5V/12V selectable header)	Audio Header	- 0
Parallel	- 0	SPDIF	- 0
SATA	- 1 (SATAII 3.0Gb/s)	HDMI-SPDIF	- 0
mPCIe	- 3	SMBUS/ I2C	- 1 (SMBUS)
	(2*Full size, 1*Full size shared with mSATA)	AT mode jumper	- 1
mSATA	- 0	Jetway Daughter	- 0
M.2	- 0	Audio Amplifier Header	- 0
Other			
Power	- 12V Lockable DC-In PWR Jack, Supports AT/ATX Mode		
Watchdog Timer	- Programmable 1 ~ 255 sec/min		
Certifications	- CE, FCC, RoHS, REACH		
Temperature	- Operating : 0■ ~ 60■, Storage : -20■ ~ 85■		